


MICRO COLOUR

CRI/TLCI / PHOTOMETRICS



R1 R2 R3 R4 R5 R6 R7 R8 R9 R10 R11 R12 R13 R14 R15 CRI TLCI CQS

100

80

60

40

20

0







Superb colour rendition with typical CRI of 95 from 2700K to 6500K

Ø

Full choice of

light control

devices - soft

boxes, lenses,

barn doors



Removable power supply via optional PSU mount

[* *] On board V-lock Full colour temp or Anton-Bauer adjustment from 2,200K to 15,000K battery adaptor available Magenta control



source using Multi-Yoke

Super Smooth

95

3200K:

5600K:

HRD low end

mode

6.0

DMX via

Fly lead XLR

connection

12,900 lx / 1,200 fc @ 1m / 3.3ft 3,150 lx / 290 fc @ 2m / 6.6ft

1,400 lx / 130 fc @ 3m / 9.8ft 790 lx / 70 fc @ 4m / 13.1ft

Ph Gang control of Dimming featuring lights using DMX or Y cables. No dimming module Dimmer board

12,340 lx / 1,150 fc @ 1m / 3.3ft 3,010 lx / 280fc @ 2m / 6.6ft

1,340 lx / 120 fc @ 3m / 9.8ft 750 lx / 70 fc @ 4m / 13.1ft

and High speed required!

R Water resistant design (IP65)

Material	Aluminium
Light Source	RGBW LED
Colour Range	CCT: 2200 - 15000K, PLUS/MINUS GREEN, HUE/SATURATION, DIRECT RGBW
CRI	Typical 95
TLCI	Typical 95
Beam Angle	20° (Half Peak Angle)
Tilt Angle	170° (Up), 80° (Down)
Rigging	3/8″ Threaded Insert. 4x rope rigging/safety points Kino Flo Twist On Style Mount Plate
Yoke	Removable (Quick Release System)
Filter Rails	2 Filter Rails for Secondary Lenses and Gels
User interface	High Precision Digital Rotary Encoder, 4 Button Keypad, Graphic LCD Display
Control	On-Board Interface, DMX-512 with Optional Adapte Cable, Optional Wired Remote Control
Dimming	0-100% with High Resolution, Super-Smooth Low End Mode
High Speed Capability	Over 5000fps Flicker Free in High Speed Mode
Synchronization	Sync Input for Triggering and Syncing to Camera Shutter
Max Ambient Temperature	40°C
Cooling	Passive - No Fans
Estimated LED Lifespan	50,000hrs (L70)
Input (Fixture)	10-32V DC, Max 8A (80W)
Input (Power Supply)	100-240V AC, 50-60Hz, Max 1.3A
Protection Class	IP65
Weight	3.4kg / 7.5lb (Excluding Yoke) 4.2kg / 9.3lb (Including Yoke)
Dimensions	223 x 207 x 108mm / 8.7" x 8.1" x 4.3" (Excluding Yoke) 300 x 331 x 108mm / 11.8" x 13.0" x 4.3" (Including Yoke)
Warranty	5 years on Fixtures, 12 months on Accessories
Certifications	CE, FCC, C-Tick

www.creamsource.com

