

CREAM | MINI+
S O U R C E



CREAM
S O U R C E

YOUR TRULY VERSATILE LIGHTING INSTRUMENT



PHOTOMETRIC DATA				
	1m / 3.3ft	2m / 6.6ft	3m / 9.8ft	4m / 13.1ft
5600K	80,300 lx / 7,460fc	34,500 lx / 3,210 fc	17,500 lx / 1,630 fc	10,200 lx / 950 fc

PHOTOMETRIC DATA				
	1m / 3.3ft	2m / 6.6ft	3m / 9.8ft	4m / 13.1ft
3200K	41,900 lx / 3,900 fc	17,400 lx / 1,620 fc	8,830 lx / 830 fc	5,170 lx / 490 fc
4000K	69,900lx / 6,500 fc	29,400 lx / 2,740 fc	15,000 lx / 1,400 fc	8,800 lx / 820 fc
5600K	44,100 lx / 4,100 fc	18,900lx / 1,760 fc	9,730 lx / 910 fc	5,700lx / 530 fc

Creamsource is a High Power LED luminaire designed for the Film and Television industries. Equally comfortable on location or in the studio, Creamsource is a truly versatile lighting tool.

With all the same features as the popular Creamsource Doppio+ in a compact 1x1 form factor, the Creamsource Mini+ is ideal for location or OB work. A large output area creates the unique quality of ‘wrapping’ your subject in soft light, while the powerful LED engine provides intensity and throw to rival a small HMI fixture. Only Creamsource can provide this mix of light properties in such a small form factor.

Precision optics provide a consistent beam with naturally soft edges, while a wide selection of light control tools are available to shape and cut the beam to achieve exactly the look you require. With exceptional build quality, it has been engineered for years of reliable service. Little wonder Creamsource is becoming an industry standard for lighting professionals around the world.

All units are supplied with the following:

- > Standard yoke for mounting on stand
- > AC Power Supply, 160W capacity, 90-250V auto-ranging
- > 3m Power header cable
- > 1 Medium diffusion lens
- > 1 Empty gel frame
- > IEC power cable for your country

Product Specifications

CRI	Typical 95, minimum 90
TLCI	Typical 95, minimum 90
Beam Angle, SPOT Lens	13° (Half Peak Angle)
Tilt Angle	170° (Up), 80° (Down)
Mounting	28mm Spigot, 5/8th Socket Adapter
Yoke	Removable (Quick Release System). Pole Operated Yoke Available on Request
Filter Rails	2 Filter Rails for Secondary Lenses and Gels
User interface	High Precision Digital Rotary Encoder, 4 Button Keypad, Graphic LCD Display
Control	On-Board Interface, 5 Pin DMX In and Thru, Wired Remote Control
Dimming	0-100%, Continuous
High Speed Capability	Over 1000fps Flicker Free in High Speed Mode
Synchronization	Sync Input for Triggering and Syncing to Camera Shutter
Max Ambient Temperature	40°C
Cooling	Passive (Silent) Under Normal Conditions. Low Noise Back-Up Fans
Estimated LED Lifespan	50,000hrs
Input (Fixture)	24-32V DC, Max 6.3A, 150W
Input (Power Supply)	90-260V AC, 50-60Hz, Max 2.0A
Protection Class	IP20
Weight	5.2kg / 11.4lbs (Including Yoke)
Dimensions	392 x 455 x 100mm / 14.7" x 15.4" x 4" (Including Yoke) 307 x 332 x 100mm / 12.5" x 13.4" x 4" (Including Yoke)
Warranty	5 year warranty on registered fixtures, 12 months on accessories
Certifications	CE, FCC, C-Tick.